

No. 240 3" Pitch — Plain Bore

Pitch	Inner width	Roller- ø
inch	inch	inch
3"	1 7/8"	1.875"

† Dimensions shown allow for standard keyway with set screw at 90°
★ Hub diameter may vary to suit bore sizes


Sprockets supplied without keyway and setscrews
unless specifically requested.



Sprocket Diameters 3" Pitch			Type A			Type B					
No. Teeth	Outside Diameter	Pitch Diameter	Catalog Number	Plain Bore	Wt. Lbs.	Catalog Number	Plain Bore	†Max. Bore	★ Hub Dia.	LTB	Wt. Lbs.
10	11.030	9.708	240A10	1 1/2	30.00	240B10	1 1/2	4 1/2	6 1/2	3 3/8	49.00
11	12.020	10.649	240A11	1 1/2	37.00	240B11	1 1/2	4 3/4	7	3 7/8	66.00
12	13.000	11.591	240A12	1 1/2	45.00	240B12	1 1/2	5 3/8	7 1/2	3 7/8	72.00
13	13.970	12.536	240A13	1 1/2	54.00	240B13	1 1/2	5 3/8	7 1/2	3 7/8	81.00
14	14.940	13.482	240A14	1 1/2	62.00	240B14	1 1/2	5 3/8	7 1/2	3 7/8	88.00
15	15.910	14.429	240A15	1 1/2	68.00	240B15	1 1/2	5 3/8	7 1/2	3 7/8	98.00
16	16.880	15.377	240A16	1 1/2	82.00	240B16	1 1/2	5 1/2	8	4 1/8	124.00
17	17.850	16.327	240A17	1 1/2	93.00	240B17	1 1/2	5 1/2	8	4 1/8	137.00
18	18.810	17.276	240A18	1 1/2	108.00	240B18	1 1/2	5 1/2	8	4 1/8	142.00
19	19.780	18.227	240A19	1 1/2	120.00	240B19	1 1/2	5 1/2	8	4 1/8	154.00
20	20.740	19.177	240A20	1 1/2	128.00	240B20	1 1/2	5 1/2	8	4 1/8	169.00
21	21.710	20.129	240A21	1 1/2	148.00	240B21	1 1/2	5 1/2	8	4 1/8	186.00
25	25.550	23.936	240A25	1 1/2	208.00	240B25	1 1/2	5 1/2	8	4 1/8	254.00
30	30.340	28.700	240A30	1 1/2	310.00						
35	35.130	33.467	240A35	1 1/2	416.00						
40	39.920	38.237	240A40	1 1/2	548.00						
45	44.700	43.007	240A45	1 1/2	702.00						
54	53.310	51.595	240A54	1 1/2	1022.00						
60	59.040	57.322	240A60	1 1/2	1268.00						

Some sizes are Made-To-Order, consult iwis for availability.

TYPE A



TYPE B

