

No. 35 $\frac{3}{8}$ " Pitch — Tapered Bushing



Pitch	Inner width	Roller- ø
inch	inch	inch
$\frac{3}{8}$ "	$\frac{3}{16}$ "	.200"

▲ Has recessed groove in hub for chain clearance

Sprockets supplied without keyway and setscrews unless specifically requested.

Type B Tapered Bushing									Tapered Bushing		
No. Teeth	Outside Diameter	Pitch Diameter	Catalog Number	Bushing	Max. Bore	Hub. Dia.	LTB	Wt. Lbs.	Bushing	Bore Range	Wt. Lbs.
18	2.352	2.160	35BTL18	1008	1	$\Delta 1 \frac{7}{8}$	$\frac{7}{8}$	.40	1008	$\frac{1}{2} - 1$	.30
19	2.472	2.278	35BTL19	1008	1	$1 \frac{13}{16}$	$\frac{7}{8}$	.50	1210	$\frac{1}{2} - 1 \frac{1}{4}$	.60
20	2.593	2.397	35BTL20	1008	1	$1 \frac{15}{16}$	$\frac{7}{8}$	.60			
21	2.713	2.516	35BTL21	1008	1	$2 \frac{1}{16}$	$\frac{7}{8}$	.70			
22	2.883	2.635	35BTL22	1210	$1 \frac{1}{4}$	$2 \frac{3}{8}$	1	.80			

Some sizes are Made-To-Order, consult iwis for availability.

TYPE B

